

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 021 950 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
26.07.2000 Bulletin 2000/30

(51) Int. Cl.⁷: **A01K 11/00**, **A61B 17/06**,
A61M 27/00

(21) Application number: **00610002.8**

(22) Date of filing: **12.01.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **22.01.1999 DK 8999**


(71) Applicant:
**SLAGTERIERNES FORSKNINGSinSTITUT
DK-4000 Roskilde (DK)**

(72) Inventors:
• **Hagdrup, Claus**
2820 Gentofte (DK)
• **Thogersen, Klaus**
2920 Charlottenlund (DK)

(54) **Tattoo-marking of an animal with multi-edged needles**

(57) The invention relates to replaceable marking elements (1) for use in the tattoo-marking of animals. The elements comprise needles (3) arranged in a pre-determined pattern such as a numeral. Several elements, together forming a supplier number, are mounted on the head of a tattooing hammer. To provide clear markings, elements are used in which the needles (3) are multi-edged at the outermost, tapering part (4) intended to be hammered into the animal's skin.

Fig. 1



EP 1 021 950 A1

Description

[0001] The present invention relates to a replaceable marking element for mounting in a hammer for the tattoo-marking of an animal, which element comprises needles arranged in a predetermined pattern. The invention further relates to a hammer for the tattoo-marking of an animal, which hammer comprises replaceable marking elements with needles arranged in a predetermined pattern.

[0002] Before pigs are sent for slaughter, the producer marks them with a supplier number. This is done with a special tattooing hammer with replaceable marking elements, each of which has needles arranged in a pattern corresponding to one figure. Together the figures of the elements form a supplier number. The producer first inks the needles on an ink pad and then administers a brief hammer blow to the animals rump, so that the needles penetrate a few millimetres into the epidermis/fat layer of the animal and deposit their ink in the indentations so formed. In certain cases the hammer is used without ink.

[0003] The mark must be sufficiently clear and robust to permit the supplier number to be read after transportation of the animal to the slaughterhouse. However, this is not always the case where the producer has not taken care to ink the needles or has not accurately executed the tattooing blow.

[0004] The purpose of the present invention is to improve the marking elements in the tattooing hammer to improve the probability of clear markings.

[0005] The marking element of the invention is characterised in that the needles are multi-edged at the outermost, tapering part intended to be hammered into the animal's skin.

[0006] The invention is based on the observation that far clearer marking of animals is obtained when the tattooing needles used are multi-edged at their outermost, tapering part which is hammered into the animal's skin. The result is that far fewer pigs will have partly or wholly illegible supplier number due to insufficient inking of the needles or badly aimed or weak hammer blows.

[0007] Particularly clear markings are obtained when needles with few edges are used. According to a preferred embodiment the outermost, tapering part of the needles will therefore be three-, four- or five-edged.

[0008] Preferably, three-edged needles are used, whereby the outermost, tapering part will preferably have three edges with similar sidefaces between the edges.

[0009] The sidefaces of the outermost, tapering part of the needles will preferably form an angle of between 4 and 20° with the longitudinal axis of the needles.

[0010] The outermost, tapering part of the needle will preferably have a length of between 2 and 15 mm and a maximum thickness of between 0.8 and 3 mm.

[0011] The marking element according to the inven-

tion comprises preferably a block with bores or embeddings for the needles in a predetermined pattern representing an alpha-numeric character.

[0012] Less force in the tattooing blow is required when marking elements are used which have fewer needles than traditional marking elements. A preferred embodiment of the element according to the invention is therefore characterised in that the number of needles is between 12 and 16, preferably between 13 and 15. If the variation in the number of needles in an alpha-numeric character set is kept within these limits, each character will mainly require the same (and lower) impact force in order to perforate the skin. This will give even more uniform and clear marking than traditional tattoos in which the average number of needles and the variation in the number of needles is greater.

[0013] The needles may be round at the part fixed to the marking element to facilitate mounting in the element.

[0014] The sidefaces of the outermost, tapering part of the needles will preferably be flat. They may also be concave in order to carry more ink between the edges of the needle. The sidefaces may also be rough or have a porous character, which may increase the quantity of ink available for tattooing.

[0015] The needles will preferably have sharp edges suitable for cutting into the skin of the animal and thus presenting a significantly larger cut area than for instance from the use of needles with a circular cross-section at the outermost, tapering part. The needles may be manufactured by traditional techniques, such as the facet-grinding of cylindrical pins.

[0016] The hammer according to the invention is characterised in that the needles are multi-edged at the outermost, tapering part intended to be hammered into the animal's skin.

[0017] Preferred embodiments of the hammer according to the invention are indicated in Claims 9 and 10.

[0018] In the following the invention will be more closely described with reference to the drawings, in which

- fig. 1 shows an embodiment of a marking element according to the invention,
- fig. 2 shows a side view of the same element, and
- fig. 3 shows an embodiment of a tattooing hammer according to the invention with six marking elements mounted on the hammer head.

[0019] Marking element 1 in figs. 1 and 2 comprises a metal block of approx. 24 x 16 x 5 mm made of, for example, zinc or aluminium. The block has sloping parts 2, which serve to fix the element to a tattooing hammer head. In the block are 14 drilled holes, arranged in a pattern to form the number "2". In each hole a needle 3 is affixed with an outermost, tapering part 4, which has three edges. Only one needle is shown in figs. 1 and 2.

The location of the other 13 needles is indicated in fig. 1 by a "+".

[0020] The needles 3 are manufactured from 10 mm long, 1.7 mm thick cylindrical steel pins which have been facet-grinded so that the outermost, tapering part 4 has the shape of a three-sided pyramid with sharp edges 5. The sidefaces or facets form an angle with the needle's longitudinal axis of approx. 8-10°. The outermost, tapering part 4 of the needles is 3-4 mm long. In other embodiments the dimensions may vary by up to ± 50% compared to the stated dimensions.

[0021] In fig. 3 the marking element together with five other elements has been mounted on the head 6 of a tattooing hammer. Each element 1 has needles arranged in a pattern representing an alpha-numeric character (a number, letter or similar, here the numbers 4, 2 and 0, made up of 13, 14 and 14 needles respectively). The number "022244" formed by the elements is a supplier number.

[0022] The elements are fixed by means of clamp rails 7 and held in position laterally by stops 8. The hammer head 6 with marking elements 1 is connected by shaft 9 to a handle 10.

[0023] The hammer is used in conventional manner, eg. for marking of pigs before they are sent for slaughter. It may be used in combination with the ink pad described in Danish Patent 169.654 B1 (Slagteriernes Forskningsinstitut) in order to achieve a one-handed system for ink supply and tattooing.

Claims

1. A replaceable marking element (1) for mounting in a hammer for the tattoo-marking of an animal, which element comprises needles (3) arranged in a predetermined pattern, **characterised** in that the needles (3) are multi-edged at the outermost, tapering part (4) intended to be hammered into the animal's skin.
2. An element according to Claim 1, **characterised** in that the outermost, tapering part (4) of the needles is three-, four- or five- edged.
3. An element according to Claim 1, **characterised** in that the outermost, tapering part (4) of the needles is three-edged with similar sidefaces between the edges (5).
4. An element according to Claim 1, **characterised** in that the sidefaces of the outermost, tapering part (4) of the needles form an angle with the needle's longitudinal axis of between 4 and 20°.
5. An element according to Claim 1, **characterised** in that the outermost, tapering part (4) of the needles has a length of between 2 and 15 mm and a maximum thickness of between 0.8 and 3mm.
6. An element according to Claim 1, **characterised** in that it comprises a block with bores or embeddings for the needles (3) in a predetermined pattern representing an alpha-numeric character.
7. An element according to Claim 1, **characterised** in that the number of needles is between 12 and 16.
8. A hammer for the tattoo-marking of an animal, which hammer comprises replaceable marking elements (1) with needles (3) arranged in a predetermined pattern, **characterised** in that, the needles (3) are multi-edged at the outermost, tapering part (4) intended to be hammered into the animal's skin.
9. A hammer according to Claim 8, **characterised** in that the outermost, tapering part (4) of the needles is three-edged with similar sidefaces between the edges (5).
10. A hammer according to Claim 8, **characterised** in that the number of needles (3) in each marking element (1) is between 12 and 16.

Fig. 1




Fig. 2





Fig. 3





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 61 0002

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (InCL7)
A	GB 2 234 420 A (BORJA MICHAEL JAMES) 6 February 1991 (1991-02-06) * the whole document *	1-10	A01K11/00 A61B17/06 A61M27/00
A	EP 0 269 164 A (STAALKAT BV) 1 June 1988 (1988-06-01) * the whole document *	1-10	
A	US 4 666 438 A (RAULERSON J DANIEL) 19 May 1987 (1987-05-19) * the whole document *	1-10	
A	EP 0 635 240 A (AMERICAN CYANAMID CO) 25 January 1995 (1995-01-25) * the whole document *	1-10	
			TECHNICAL FIELDS SEARCHED (InCL7)
			A01K
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 12 Apr11 2000	Examiner Weber, G
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1500 (04/98) (P/0001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 61 0002

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

12-04-2000

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
GB 2234420	A	06-02-1991	NONE		
EP 0269164	A	01-06-1988	NL	8602835 A	01-06-1988
			DK	577887 A	10-05-1988
US 4666438	A	19-05-1987	NONE		
EP 0635240	A	25-01-1995	US	5403344 A	04-04-1995
			CA	2128472 A	23-01-1995
			DE	69414043 D	26-11-1998
			DE	69414043 T	18-03-1999
			ES	2123686 T	16-01-1999

EPO FORM P/0018

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

